

BRC-T1790B 电子平头锁眼机


Electronic lockstitch Buttonholing Machine



多种花样选择 升级方便
Patterns are Easy to Update



头部无油 清洁缝制
Dry Head System



底缝工艺 花样不变形
Basting Stitch Function



散热系统 低温耐用
Cooling System, Long Durability

机器信息附表 SPECS SCHEDULE

		 (mm)							 (mm)	 (S.p.m)	 (mm)	 NW/GW (kg)
BRC-T1790BS-1		25×4	DPX5 12#	1	1/4"~3/4"	2	0.2~2.5	220V	17	4200	780×390×830	56/77
BRC-T1790BS-2		35×5	DPX5 12#	1	1/4"~1"	2	0.2~2.5	220V	17	4200	780×390×830	56/77
BRC-T1790BS-3		41×5	DPX5 12#	1	1/4"~1 1/4"	2	0.2~2.5	220V	17	4200	780×390×830	56/77
BRC-T1791BS		70×5	DPX5 12#	1	1/4"~1 1/4"	2	0.2~2.5	220V	17	4200	780×390×830	56/77
BRC-T1792BS		120×5	DPX5 12#	1	1/4"~1 1/4"	2	0.2~2.5	220V	17	4200	780×390×830	56/77
BRC-T1790BK-1		25×4	DPX5KN 11#	1	1/4"~3/4"	2	0.2~2.5	220V	17	4200	780×390×830	56/77
BRC-T1790BK-2		35×5	DPX5KN 11#	1	1/4"~1"	2	0.2~2.5	220V	17	4200	780×390×830	56/77
BRC-T1790BK-3		41×5	DPX5KN 11#	1	1/4"~1 1/4"	2	0.2~2.5	220V	17	4200	780×390×830	56/77
BRC-T1791BK		70×5	DPX5KN 11#	1	1/4"~1 1/4"	2	0.2~2.5	220V	17	4200	780×390×830	56/77
BRC-T1792BK		120×5	DPX5KN 11#	1	1/4"~1 1/4"	2	0.2~2.5	220V	17	4200	780×390×830	56/77